Trinity



A decorative modern circular polo pendant mounted LED with options of body sizes.

- Corridors
- Offices
- Communal Areas
- Education
- Public Places



Features

- Rolled steel body
- PMMA UV stabilized acrylic
- Epoxy powder coated RAL9003 (Other colour options available on request)
- IP40

Options


- Integrated 3hr emergency -Standard (M3) Self-Testing Emergency (STE)
- DALI Monitored Emergency (DA3)
- DALI (DA)
- Casambi Wireless Control (BTC)
- Micro-Prism UGR<19 diffuser (MPO)
- Suspension kit (SUS/2M)



Trinity



Dimensions



D – 600 / 900 / 1200 / 160mm x H - 80mm



Product Code

TRS-17-4K-WH	Trinity, 17w, 4K, 2,014lm. 600mm, body finished RAL9003
TRS-24-4K-WH	Trinity, 24w, 4K, 2,744lm. 600mm, body finished RAL9003
TRS-35-4K-WH	Trinity, 35w, 4K, 3,772lm. 600mm, body finished RAL9003
TRS-27-4K-WH	Trinity, 27w, 4K, 3,295lm. 900mm, body finished RAL9003
TRS-38-4K-WH	Trinity, 38w, 4K, 4,491lm. 900mm, body finished RAL9003
TRS-55-4K-WH	Trinity, 55w, 4K, 6,172lm. 900mm, body finished RAL9003
TRS-35-4K-WH	Trinity, 35w, 4K, 4,394lm. 1200mm, body finished RAL9003
TRS-50-4K-WH	Trinity, 50w, 4K, 5,987lm. 1200mm, body finished RAL9003
TRS-73-4K-WH	Trinity, 73w, 4K, 8,231lm. 1200mm, body finished RAL9003
TRS-49-4K-WH	Trinity, 49w, 4K, 6,225lm. 1600mm, body finished RAL9003
TRS-70-4K-WH	Trinity, 70w, 4K, 8,482lm. 1600mm, body finished RAL9003
TRS-103-4K-WH	Trinity, 103w, 4K, 11,660lm. 1600mm, body finished RAL9003

^{**} Suffix end of code (M3) for emergency facility or (DA) for DALI/Switch DIM or (BTC) for Casambi Wireless Control or (MW1) Microwave sensor



^{**}Example: TRS-38-4K-WH-BTC Trinity 38w, 4,191lm, 4K, white c/w Casambi